

Host a DevOps exam using NixOS

Deploy a Bastion host and a KVM virtual machine per student in order for them to deploy a website which will be auto-validated.

Yvan SRAKA, Ryan LAHFA

Host a DevOps exam using NixOS

- ▶ DevOps students have to test their skills in a real-world exam, what's better than scripting it using NixOps in order to reuse it?
- ▶ They will be provided with their own user account on the Bastion and access to a jump user account, WireGuard will be auto-configured on the host to enable access to their KVM host directly.
- ▶ The main point is controlling the KVM guests “declaratively” and giving choice to the students to choose their guest OS: Debian or NixOS.
- ▶ We will see how we can easily generate Nix expression from a scripting language, e.g. Python, and feed it to a NixOps deployment.

Disclaimer: *all this is incomplete and experimental!*

This was tried during a real exam this summer, but it's very alpha-quality and had to get a lot of last-minute fixes due to external issues (e.g. disks dying...)

Git repository

The full code can be found here¹, it's still a bit messy...

\nix folder contains files on which will focus this talk:

- ▶ `student-setup.nix` is generated by `generate-setup.py` (that rely on `nix-expr.py`) from students data.
- ▶ `deploy.sh` push on our setup `exam.nix`, `student.nix`, `kvm-guests.nix` and `student-setup.nix`

¹<https://git.newtype.fr/yvan/devops-exam-model>

deploy.sh

```
#!/usr/bin/env bash

echo "[+] Regenerating of the setup"
python3 generate_setup.py

echo "[+] Sending Nix files"
rsync --inplace --temp-dir=/tmp -avPz *.nix \
      yvan@bastion:/etc/nixos/

echo "[+] Rebuilding of the exam machine"
ssh -t yvan@bastion "sudo nixos-rebuild switch"
```

generate_setup.py (subset of)

```
def students(csv_filename):
    with open(csv_filename, 'r', newline='') as csvfile:
        ereader = csv.reader(csvfile, delimiter=';')
        next(ereader) # exhaust header.
        for index, student in enumerate(ereader):
            name, surname, email, username = student
            wg_pubkey, wg_privkey = wireguard_parameters()
            keys = read_keys(username)
            yield {
                "surname": surname,
                "name": name,
                "email": email,
                "username": username,
                "keys": keys,
                "wireguardPublicKey": wg_pubkey,
                "wireguardPrivateKey": wg_privkey,
            }
```

student-setup.nix (generated)

```
ltorvalds = {
  email = "torvalds@linux-foundation.org";
  guestOperatingSystem = "debian";
  index = 42;
  keys = [
    "ssh-ed25519 ... torvalds@linux-foundation.org"
  ];
  name = "Linus";
  surname = "Torvalds";
  username = "ltorvalds";
  wireguardPrivateKey = "0ECE2Js+RkxQVTyJ9BvZBODjpEGnWMy1";
  wireguardPublicKey = "3o9Dhmrrql/5PZEhi5kS+Fob1m8rN70S";
};
rinstallman = { ... }
```

student.nix (subset of)

```
mkGuest = name: student: {
  memory = "1G";
  netDevice = "tap${toString student.index}";
  vncDisplay = "localhost:${toString student.index}";
  operatingSystem = student.guestOperatingSystem;
};

services.kvmGuests = {
  enable = true;
  guests = mapAttrs mkGuest cfg.students;
};

# Create users for each student + management/jump accounts
users.users = (mapAttrs mkBastionUser cfg.students) // ({
  jump = mkJumpUser cfg.students;
  admin = adminUser;
});
```

Q/A